

D23x30 S3 NAVIGATOR®

HORIZONTAL DIRECTIONAL DRILL



THE NEW QUIET. With a 100 dB(A) guaranteed sound power level and an operator ear rating of 80.6 dB(A), the D23x30 S3 makes a quiet working environment possible, creating less neighborhood disturbance and enabling easier communication among the crew.



COMPACT, YET POWERFUL. The D23x30 S3 features a short, narrow design, while its 100 hp (75 kW) Deutz engine offers the power operators need when working in tough ground conditions.



MAXIMIZE PRODUCTIVITY. With 24,000 lb (106.8 kN) of thrust/pullback and 3,000 ft-lb (4067.5 Nm) of rotational torque, the D23x30 S3 offers a sizable increase in power over its predecessor, the D20x22 Series II — helping to maximize machine and jobsite productivity.



NEED FOR SPEED. With a carriage speed of 206 ft/min (62.8 m/min) and a rotational speed of 219 rpm, the D23x30 S3 helps contractors install more linear feet per day, maximizing jobsite productivity and efficiency.



GET TO WORK FASTER. The D23x30 S3 can track up to 3.3 mph (5.3 km/h) helping operators get into position for their next shot more quickly, while making it easier to climb slopes and make sharp turns.



COMMON CONTROLS. To assist in operator efficiency and training, the D23x30 S3 features the dual joysticks and common control platform found up and down the Navigator horizontal directional drill lineup. The system design uses less wiring and fewer fuses for greater reliability.

D23x30 S3 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

GENERAL WEIGHTS AND DIMENSIONS

Minimum transport length: 17.4 ft (5.3 m)

Minimum transport width: 52.5 in (133.4 cm)

Minimum transport height: 75 in (190.5 cm)

Weight: 14,500 lb (6,577 kg)

ENGINE OPTION ONE

Make and model: Deutz TCD3.6L4

Fuel type: Ultra low sulfur diesel

Maximum engine rpm: 2,000 rpm

Gross horsepower: 100 hp (75 kW)

Displacement: 220 cu in (3.6 L)

Cooling method: Liquid

Aspiration: Turbo

Certification Family (EPA/EU): Tier 4F/Stage V

ENGINE OPTION TWO

Make and model: Deutz TCD3.6L4

Fuel type: Diesel <2,000 ppm sulfur content

Maximum engine rpm: 2,000 rpm

Gross horsepower: 100 hp (75 kW)

Displacement: 220 cu in (3.6 L)

Cooling method: Liquid

Aspiration: Turbo

Certification Family (EPA/EU): Tier 3/Stage IIIA

OPERATIONAL

Thrust/pullback: 24,000 lb (106.8 kN)

Maximum carriage speed at max engine rpm: 206 ft/min (62.8 m/min)

Maximum spindle torque [low at max engine rpm - 2.06 in (5.2 cm) drill rod]: 2,600 ft-lb (3,525.1 Nm)

Maximum spindle torque [low at max engine rpm - 2.375 in (6 cm) drill rod]: 3,000 ft-lb (4,067.5 Nm)

Maximum spindle speed at max engine rpm: 219 rpm

Minimum bore diameter: 4 in (10.2 cm)

Maximum ground drive speed at max engine rpm (fwd): 3.3 mph (5.3 km/h)

Noise level at operator's ear: 80.6 dB(A)

Drill rack angle: 12-18° (21.3-32.5%)

FLUID CAPACITIES

Fuel tank: 35 gal (132.3 L)

Antifreeze tank capacity: 2.5 gal (9.45 L)

Onboard optional water tank: 25 gal (94.5 L)

DRILLING FLUID SYSTEM

Maximum flow: 35 gpm (132.3 L/min)

Maximum pressure: 1,300 psi (89.6 bar)

FEATURES

Breakout system: Standard hydraulic vise

Drilling lights: Optional

Flow indicator: Standard

Stakedown system: Standard

Strike Alert: Standard

Remote Lockout: Standard

DRILL PIPE OPTION ONE

Type: Firestick® drill rod

Length: 10 ft (3 m)

Rod diameter: 2.06 in (5.2 cm)

Weight: 62 lb (28.1 kg)

Bend radius: 101.9 ft (31.3 m)

Onboard capacity: 480 ft (146.3 m)

DRILL PIPE OPTION TWO

Type: Firestick drill rod

Length: 10 ft (3 m)

Rod diameter: 2.375 in (6 cm)

Weight: 73 lb (33.1 kg)

Bend radius: 108.2 ft (33 m)

Onboard capacity: 400 ft (121.9 m)

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Deutz is a trademark of Deutz Ag Corporation. © 2022 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

