

T755III TRENCHER



SMARTTEC ELECTRONIC CONTROL SYSTEM. SmartTEC performance software helps optimize productivity with real-time machine control prompts. Monitor and record functions encourage proactive machine maintenance and operator performance analysis. Available on all Vermeer TEC® Plus computer-aided control system-equipped machines.



ELEVATING ROPM CAB. The elevating rollover protective module cab features LEXAN glass, filtered and pressurized air, heating and air-conditioning. The cab's vantage point allows a virtually unrestricted view of the boom, trench and conveyor.



OPTIONAL AUTO TILT TRACK. An oscillating track frame allows the track to follow the ground's contour ensuring a vertical trench on slopes up to 10 degrees.



VANTAGE TRACK. Relax in the confidence that your investment is protected and your entire closed-loop hydrostatic system is covered with either a 3-year/3000-hour or 5-year/5000-hour extended care service program.



ROTARY POWER TRENCHER DRIVE MOTOR. A rotary power trencher drive motor and splined headshaft produce low-speed and high torque which provide superior ground penetration and low chain wear for better production results.



FULL FUNCTION REMOTE CONTROL. The T755 Commander® 3 is available with a wireless remote control that can provide full operator function remotely.

T755III TRENCHER

GENERAL DIMENSIONS

Approach angle: 22°

Height: 10' (3 m)

Length range: 28' – 33.6' (8.5 m – 10.2 m)

Weight range (tractor plus trencher attachment): 49,000 lb – 75,000 lb (22,226 kg – 34,019.4 kg)

Width range: 8.2' – 8.5' (2.5 m – 2.6 m)

ENGINE OPTION ONE

Make and model: Caterpillar C9 ACERT

Gross horsepower: 275 hp (205 kW)

Engine rpm: 2200

Fuel consumption @ full load: 14.7 gph (55.6 L/hr)

EPA certification family: Tier 3

ENGINE OPTION TWO

Make and model: John Deere 6090H

Gross horsepower: 275 hp (205 kW)

Engine rpm: 2200

Fuel consumption @ full load: 13.2 gph (50 L/hr)

EPA certification family: Tier 4 Final (Stage IV)

TRACKS

Ground pressure: 8.9 psi – 12.5 psi (61.4 kPa – 86.2 kPa)

Tilt track with Auto Level available: Yes, max angle 12°

Track length: 11.8' (3.6 m)

Track pad type: Single, double, triple or polyurethane grouser

Track pad width: 20" (50.8 cm) or 24" (60.9 cm)

Track size: D5

Travel speed max: 170 fpm (51.8 m/min)

Service brakes: Hydrostatic

CONVEYOR

Belt width: 24" (61 cm)

Max conveyor belt speed: 1118 fpm (340.8 m/min)

Conveyor belt style: Cleated or finger-type

Conveyor length: 8' or 12' (2.4 m or 3.7 m)

Conveyor shift available: Yes

Conveyor shift distance: 14" or 66" (35.6 cm or 167.6 cm)

Conveyor style: Curved

Discharge direction: Right or left

Discharge height: 55" or 68" (139.7 cm or 172.7 cm)

CAB

Air conditioner/heater: Yes

Air suspension seat: No

AM/FM stereo with weather band: Yes

Elevating: Yes

Pressurized/filtered air: Yes

Rollover protective module (ROPM): Yes

Level II FOPS: Yes

TRENCHER ATTACHMENT

Boom depth options: 5', 6', 8' or 10' (1.5 m, 1.8 m, 2.4 m or 3 m)

Boom top rollers: Optional

Chain speed range: 397 fpm – 724 fpm (121 m/min – 220.7 m/min)

Cutting width range: 14" – 36" (35.6 cm – 91.4 cm)

End idler diameter: 40" (101.6 cm)

OPTIONS

Loadout conveyor

Remote control

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Commander and TEC are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. John Deere is a trademark of Deere and Company. Caterpillar is a trademark of Caterpillar Inc. Lexan is a trademark of Sabic Innovative Plastics IP BV. © 2016 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

